- 7		- 4	1
- /		=	_
- 1		=	
1-		-	C
_	_	-	σ
Ė	State	-	ċ
_		=	_
~ ~		===	
==	200	=	٠
2		-	٠
			Ğ
0		_	
	=	_	

DETERM

lug.

11

FORM PTO-139 (REV. 9-2001)

INTERNATIONAL APPLICATION NO. | INTERNATIONAL FILING DATE

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371

ATTORNEY 'S DOCKET NUMBER

2625-1-002

U.S. APPLICATION NO. (If known, see 37 CFR 1.5 10

PRIORITY DATE CLAIMED

PCT/AU00/00367	April 20, 2000	Apri
TITLE OF INVENTION		

122, 1999 T TREATED CLOSURES 3

APPLICANT(S) FOR DO/EO/US Phillip MACKIE; Darren LANGE; Russell JOHNSON; Leanne BRITCHER: Janis MATISONS; Terry WILKS; Rosalind MA; Mark FRANSON

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

- This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.
- This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.
- 3. X This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below.
- 4. The US has been elected by the expiration of 19 months from the priority date (Article 31).
- 5. X A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - X is attached hereto (required only if not communicated by the International Bureau).
 - X has been communicated by the International Bureau.
 - is not required, as the application was filed in the United States Receiving Office (RO/US).
- 6. X An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
 - X is attached hereto.
 - has been previously submitted under 35 U.S.C. 154(d)(4).
- 7. X Amendments to the claims of the International Aplication under PCT Article 19 (35 U.S.C. 371(c)(3))
 - are attached hereto (required only if not communicated by the International Bureau).
 - have been communicated by the International Bureau.
 - have not been made; however, the time limit for making such amendments has NOT expired.
 - have not been made and will not be made.
- 8. An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371 (c)(3)).
- 9. X An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). UNEXECUTED
- 10. An English lanugage translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11 to 20 below concern document(s) or information included:

- An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
- An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
- 13. X A FIRST preliminary amendment.
- A SECOND or SUBSEQUENT preliminary amendment. 14.
- 15. A substitute specification.
- 16. A change of power of attorney and/or address letter.
- 17. A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
- 18. A second copy of the published international application under 35 U.S.C. 154(d)(4).
- 19. A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
- 20. X Other items or information: Four (4) Sheets of Drawings (Figs. 1A-2D);

Copy of International Search Report

EXPRESS MAIL CERTIFICATE NO.: EL 920250554 US DATE OF DEPOSIT: October 22, 2001

-	indi Para
į	PROP
1	130
-	京 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日
÷	1
-	r
1	neil
-	nis
1	1
i	100
1	100
-	'n,
1	ď
1	189
-1814	「 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日

U.S. ATICOTON	J'5'5'1		TERNATIONAL APPLICATION NO			ATTORNEY'S DO 2625-1-00	
21. The following fees are submitted:			CAI	CULATIONS	PTO USE ONLY		
BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)): Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO							
International prelin USPTO but Intern	ninary examination ational Search Rep	fee (3 ort pre	7 CFR 1.482) not paid to pared by the EPO or JPC	\$\$890.00			
International prelir but international se	ninary examination earch fee (37 CFR 1	fee (3 1.445(a	7 CFR 1.482) not paid to (2)) paid to USPTO	USPTO \$740.00			
International prelir but all claims did n	ninary examination ot satisfy provision	fee (3 s of PC	7 CFR 1.482) paid to US T Article 33(1)-(4)	SPTO \$710.00			
and all claims satis	fied provisions of F	CT A	7 CFR 1.482) paid to US ticle 33(1)-(4) BASIC FEE AMO	\$100.00	\$ 1.0	040.00	1
			or declaration later than		3 1,0	40.00	-
months from the ear	liest claimed priori	ty date	(37 CFR 1.492(e)).		s		
Total claims	NUMBER FILE		NUMBER EXTRA	RATE	\$		
Independent claims	1 - 3		0	x \$18.00	\$.00	ļ
MULTIPLE DEPEN				x \$84.00 + \$280.00	\$.00	
MODINEL BENEAU			F ABOVE CALCU			040.00	
Applicant claim	ns small entity statu	s. See	37 CFR 1.27. The fees	indicated above		340.00	
are reduced by	1/2.			+	\$	520.00	
			SU	BTOTAL =	\$	520.00	
Processing fee of \$1 months from the ear	Processing fee of \$130.00 for furnishing the English translation later than 20 30 months from the earliest claimed priority date (37 CFR 1.492(f)).						
			TOTAL NATIO		\$	520.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +				\$			
TOTAL FEES ENCLOSED =			\$:	520.00			
			Amou	mt to be efunded:	\$		
						charged:	\$
a. X A check in the amount of \$ 520.00 to cover the above fees is enclosed.							
b. Please charge my Deposit Account No. in the amount of \$ to cover the above fees. A duplicate copy of this sheet is enclosed.							
c. X The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 11-1153 A duplicate copy of this sheet is enclosed.							
 d. Fees are to be charged to a credit card. WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038. 							
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b)) must be filed and granted to restore the application to pending status.							
SEND ALL CORRESPO	NDENCE TO:			λ	1-	taV(2	
DAVID A. JAC	KSON			SIGNATU	(dea)	actors.	<u> </u>
KLAUBER & J					' (.)	ı
411 Hackensack				David A	. Jae	CSOM	
Hackensack, Ne		l					
(201) 487-5800				26,742	MT ON TO		
				REGISTRA	HONN	IUMBER	

PATENT 2625-1-002

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANTS

Phillip MACKIE et al

APPLICATION NO. :

PCT/AU00/00367

FILED

April 20, 2000

FOR

TREATED CLOSURES 3

PRELIMINARY AMENDMENT

ASSISTANT COMMISSIONER FOR PATENTS

BOX PCT

WASHINGTON, D.C. 20231

Sir:

Prior to calculating the fees pursuant to the entry into the National Phase of the aboveidentified Application, please amend the claims as follows:

IN THE CLAIMS:

Please enter and consider Claims 1-12 appended hereto in place of the Claims 1-15 submitted and attached to the original International Application as filed under the Patent Cooperation Treaty.

REMARKS

Attached Claims 1-12 are submitted herewith in place of the claims that were included with the original International Application as filed, and represent revisions to such claims so as to place them in greater conformity with U.S. practice and claim format. The substance of the attached claims is commensurate in scope with that of the Application as filed, and merely seeks to better conform with the requirements for claims that are imposed under the U.S. Patent Laws.

In all of the respects, the Application as filed is believed to be in proper form, and prompt and favorable processing before the U.S. Patent and Trademark Office is accordingly courteously solicited.

Entry of the foregoing amendments and early and favorable processing in the National Phase before the United States Patent and Trademark Office is courteously solicited.

Respectfully submitted,

DAVID A JACKSON Attorney for Applicant(s) Registration No. 26,742

KLAUBER & JACKSON 411 Hackensack Avenue Hackensack, NJ 07601 (201) 487-5800

REPLACEMENT CLAIMS

WE CLAIM:

- 1. A method for producing a coating or diffusion layer on a substrate for use in contact with a food product or beverage, said coating or diffusion layer preventing or inhibiting passage therethrough of flavour-active or odour-active compounds, and said method comprising applying to the surface of said substrate an effective amount of a copolymer comprising a flexible component and a retentive component, said flexible component being sufficiently flexible to allow the coated substrate to undergo compression and recovery and said retentive component being able to bind with or otherwise retain flavour-active or odour-active compounds.
- A method according to claim 1, wherein said substrate is selected from the group consisting of a bottle closure, packaging or wrapping material, a bottle and other containers.
- A method according to claim 1, wherein said substrate is a natural or synthetic
 cork, and said coating or diffusion layer prevents or inhibits passage of flavouractive or odour-active compounds from said cork to an alcoholic beverage in contact
 with said cork.
- A method according to claim 3, wherein said flexible component is sufficiently flexible to allow the coated cork to be compressed and then to recover during a bottling process.
- A method according to claim 1, wherein said flavour-active compounds are trichloroanisoles (TCA).
- A method according to claim 1, wherein said copolymer is selected from the group consisting of graft, alternating and block copolymers.
- A method according to claim 1, wherein said flexible component is formed from silicon-based monomers.

- 8. A method according to claim 1, wherein said copolymer is selected from the group consisting of polyvinylacetate (PVA) copolymers, polyurethane copolymers and ionomers, terephthalate copolymers, styrene–acrylonitrile (SAN)/ acrylonitrile-butadiene–styrene (ABS) copolymers, (vinylidene) copolymers, epoxy copolymers, amide copolymers, Bisphenol copolymers, Bisphenol A (BPA) epichlorohydrin copolymers, poly (methyl) methacrylate copolymers, poly(methacrylic acid) copolymers, cellulose copolymers, polyethylene vinyl alcohol copolymers, silane copolymers and siloxane copolymers.
- A method according to claim 8, wherein said copolymer is a polyvinylacetate (PVA) copolymer.
- 10. A method according to claim 8, wherein said copolymer is selected from the group consisting of silane and siloxane copolymers, comprising functionalities selected from the group consisting of polyethyleneglycol (PEG), isoprene, butadiene, lactone, amino, terephthalate, amino acid, heterocyclic, hydride (SiH), thiol and epoxy functionalities.
- 11. A coated substrate produced according to the method of claim 1.
- 12. A coated cork produced according to the method of claim 1.

4/12/

TREATED CLOSURES 3

BACKGROUND TO THE INVENTION

This invention provides improved closures for use in connection with food or beverages. One application is in relation to closures for wine bottles.

Wine bottles have traditionally been stoppered with corks made from natural cork material. However, this material can be subject to initial flaws, or deteriorate in use, resulting in contamination or spoilage of the wine. For example, oxidation of the wine, due to permeation of oxygen through the cork into the wine, results in vinegar flavour. "Cork taint", due to the presence of trichloro-anisoles (TCA) and other undesirable flavour-active or odour-active compounds in the cork, imparts a musty or mouldy smell and flavour to the wine. Leakage can also be a problem. Furthermore, cork is a relatively expensive material, as most supplies still come from Portugal.

None of the alternatives to natural corks proposed to date have been entirely satisfactory.

Synthetic "corks" and screw-cap stoppers have been used in the wine industry, but have not yet been tested adequately over the prolonged storage periods of quality red wines. There is some indication, however, that synthetic "corks" may impart flat flavours to wines. Furthermore, there is considerable consumer resistance to use of synthetic "corks" and screw - cap stoppers, particularly for quality wines. A further disadvantage is that synthetic "corks" are generally far more difficult to remove, using a hand-operated corkscrew, than natural corks.

Accordingly, there have been numerous attempts to improve on natural cork stoppers, by coating or impregnating them.

The first cork coatings were simply lubricants such as paraffin and Vaseline. These merely ensured that the cork was easier to insert into the bottle and later remove, without disintegration. The other problems associated with cork stoppers were not addressed.

Currently, materials used in surface treatment of corks include oils and silicone resins, emulsions of various formulations, as well as some synthetic coatings. These coatings do prevent leakage of the wine, but do not provide a barrier against taint and oxidation.

Many of these coatings also present problems with the coating coming off the cork and leaving an oily layer on the wine surface.

Hybrid corks have been moulded from natural cork and synthetic cork cells made from a synthetic polymer. The synthetic cells fill the gaps between the cork cells, and a binding agent (such as polyurethane) is used to bind the cells together. However, hybrid corks have to date proved unsatisfactory, as they often leak and can disintegrate and be difficult to extract from a bottle.

The present invention provides an improved closure having a surface coating or diffusion layer comprising an appropriate polymer. This coating or diffusion layer has many properties which are of benefit when used (for example) in relation to corks (either natural or synthetic) for wine bottles. The coating or diffusion layer limits oxygen permeability, inhibits or prevents the diffusion of trichloro-anisoles (TCA) and other flavour-active or odour-active compounds from the cork to the alcoholic beverage, adheres strongly to the cork and/or penetrates into the surface of the cork, is sufficiently flexible to be capable of withstanding compression and decompression during the corking process, enables the coated cork to be readily extracted from the bottle, reduces or prevents wine leakage, is resistant to sulphur dioxide, and has long life under alcoholic beverage conditions.

These coatings or diffusion layers are also applicable to substrates other than cork (eg packaging and wrapping materials) which are in contact with food products or beverages.

SUMMARY OF THE INVENTION

According to the present invention, a copolymer comprising a flexible component and a retentive component is applied as a surface coating or diffusion layer to a substrate for use in contact with food products or beverages, said flexible component being sufficiently flexible to allow the coated substrate to undergo compression and recovery (eg so as to allow a coated cork according to the present invention to be compressed and then to recover during the bottling process) and said retentive component being able to bind with or otherwise retain flavour-active or odour-active compounds (commonly known as taint compounds). The flexible component of the copolymer may be silicon-based, but the copolymers of the present invention are not restricted to those comprising silicon-based monomers. Other flexible monomers providing the necessary requirements for the coating may also be used. Two or more copolymers may be blended together to achieve the desired properties.

The substrate may, for example, be a bottle closure (such as a cork), packaging and wrapping materials (such as packaging for cheese), or a bottle or other container.

As mentioned above, the copolymer comprises a flexible (eg silicon-based) component and a retentive component that retains flavour-active or odour-active compounds. This multi-component polymer structure acts as a partial physical barrier to the passage of gases and undesirable flavour-active or odour-active compounds, whilst having the physical properties (in particular, flexibility) required during the treatment and packaging processes. In particular, the polymer coating or diffusion layer of the present invention will prevent any undesirable flavour-active or odour-active compounds migrating from a cork to an alcoholic beverage. The copolymer is also selected for other advantageous properties, such as adhering

WO 00/64649 PCT/AU00/00367

4

strongly to the substrate and/or penetrating into the surface of the substrate. Furthermore, if the substrate is a cork, the copolymer coating or diffusion layer must enable the coated cork to be readily extracted from the bottle, prevent wine leakage, and have long life under alcoholic beverage conditions. Preferably, the copolymer coating or diffusion layer will also be resistant to sulphur dioxide and changes in pH.

DETAILED DESCRIPTION OF THE INVENTION

The copolymers of the present invention may be graft, alternating or block copolymers, or mixtures thereof. Suitable copolymers are described in the following references:

- J.Wen, G. L. Wilkes, Polymer Bulletin, 1996, 37, 51-57
- J. Hazziza-Laskar, G. Helary, G. Sauvet, J. Appl. Polym. Sci., 1995, <u>58</u>, 77-84Tezuka et. al., Macromolecules, 1995, 28(24), 8251-8258
- P. Schofield, C. Cohen, C. K. Ober, Polymer Gels & Networks, 1998, <u>6</u>(3-4), 291-300
- T. Furuzuno, K. Seki, A. Kishida, T. Ohshige, K. Waki, I. Maruyama, M. Akashi, J. Appl. Polym. Sci.,1996, <u>59</u>, 1059-1065
- D. Spridon, L. Panaitescu, D. Ursu, C. V. Uglea, I. Popa, R. M. Ottenbrite, Polymer International, 1997, 43, 175-181
- J. C. Schmidhauser, K. L. Longley, J. Appl. Polym. Sci., 1990, <u>39</u>, 2083-2096
- L. Lestel, H. Cheradame, S. Boileau, Polymer, 1990, 31, 1154-1158
- G. E. Hahn, K. D. Klein, I. Yilgor, C. Could; In <u>Silicone-Containing Polymers</u>; Editor, R.G. Jones; The Royal Society of Chemistry: Cambridge, UK; 1995; pp 81-87
- M. A. Sherman, I. P. Kennedy, I. Appl. Polym. Sci., 1998, 30, 1891-1899

Examples of such copolymers are:

polyvinylacetate (PVA) copolymers polyurethane copolymers and ionomers terephthalate copolymers WO 00/64649 PCT/AU00/00367

5

styrene-acrylonitrile (SAN)/acrylonitrile-butadiene-styrene (ABS) copolymers
(vinylidene) copolymers
epoxy copolymers
amide copolymers
Bisphenol copolymers
Bisphenol A (BPA) – epichlorohydrin copolymers
poly (methyl) methacrylate copolymers
poly (methacrylic acid) copolymers
cellulose copolymers
polyethylene vinyl alcohol copolymers

silane and siloxane copolymers, eg comprising polyethylene glycol (PEG), isoprene, butadiene, lactone, amino, terephthalate, amino acid, heterocyclic,

isoprene, bundene, necone, annio, cerepitalatae, annio asia, necose

hydride (SiH), thiol or epoxy functionalities,

and mixtures thereof, provided that they comprise the required flexible and retentive components (as defined above).

PVA and functionalised siloxanes (eg comprising SiH or amino groups) have been found to be particularly suitable components of the copolymers.

Modifications of the polymers may be necessary to improve resistance to reactions with various components of the food product or beverage (eg wine).

The polymer coatings and diffusion layers of the present invention may be used in conjunction with lubricants, such as paraffin or Vaseline, to make the coated cork easier to insert into a bottle and later extract.

The method of applying the copolymer to the substrate will be dependent on the nature of the copolymer and of the substrate, and will include such conventional processes as film formation, adsorption from solution, reactive-adhesion to cork, melt polymer application (eg thermoforming, vacuum forming and plasma

6

polymerisation), UV curing and Corona discharge processes. The polymers may also be components of multi-layer laminate structures.

Preferably, the substrate (eg cork) is prewashed with a solution (eg ethanol, water or a mixture of ethanol and water) and then dried before coating, to remove any surface contamination.

The following examples form an overview of some of the technologies which may be used. These examples are illustrative, but not restrictive, of the present invention.

DESCRIPTION OF THE DRAWINGS

Figs 1A - C are the results of Scanning Electrode Microscopy (SEM) of the coating of Example 3.

Figs 2A - D are the results of SEM of the coating of Example 8.

SENSORY EVALUATION TESTS

Corks were spiked with TCA by soaking 100 corks in 1.5 litres of 100mg/L of solution of TCA in absolute ethanol for 24 hours. The corks were then removed from the solution and allowed to dry in a 40°C oven for 24 hours before being submitted for sensory evaluation to ensure that the corks have TCA odours. These corks were then coated with the coatings given below and sent for sensory evaluation.

Coated TCA spiked corks were immersed in approximately 150mL of white wine for 24 hours. The wine was evaluated for unacceptable odours by a team of experts, being a group of no less than three qualified trained sensory evaluators. The samples were given a rating of between 1 and 4. A rating 1 indicated a slight odour, rating 2 a moderate odour, rating 3 a strong odour and rating 4 a very strong odour. A rating of 2 or less was acceptable. The sensory evaluation tests related primarily to TCA

odours, which were indicative of likely problems relating to undesirable flavour- and odour-active compounds.

COATINGS

A TCA spiked cork and a non-TCA cork were coated with the coatings described below and subjected to sensory evaluation.

Example 1: Polyurethane

A mixture of 1,3-Bis(aminopropyl)tetramethyldisiloxane (3g, 0.012mol) and caprolactone (4.1g, 0.036mol) was heated to 75°C under nitrogen before the catalyst, stannous octoate (0.1mL), was added. The mixture was refluxed for 2 hours at 75°C before the temperature was raised to 140°C for a further 1.5 hours. The product was then allowed to cool.

A mixture of the above product (7g, 0.012mol), dimethylolpropionic acid (0.8g, 5.95×10^{-3} mol), hexamethylenediisocyanate (3g, 0.018mol), acetone (20mL) and dibutyltin dilaurate (0.1mL) was stirred under nitrogen at 35° C for 15 minutes and then allowed to cool. Triethylamine (1mL) was added and stirred continuously for 30 minutes, before carefully adding 30mL of distilled water. The acetone was removed *in vacuo* to give the water-dispersed polyurethane.

Corks were dipped into this coating and allowed to cure in an oven at 40°C for 24 hours.

Sensory evaluation tests gave a rating of 2 or less.

Example 2: Polybutadiene / Triethoxysilane Copolymer

A mixture of polybutadiene (Mn = 400, 9.1g, 0.023mol), triethoxysilane (4.2g, 25mmol) and H₂PtCl₆ (0.8ml.), in toluene, was refluxed for 24 hours under nitrogen

WO 00/64649 PCT/AU00/00367

8

at 110°C. The solution was then allowed to cool, and solvent and excess triethoxysilane was evaporated under vacuum to give a pale yellow oil as a product.

The polymer was diluted to 25% (v/v) with ethanol and the cork was dipped into this coating and then dried at 40° C for 24 hours.

Sensory evaluation tests gave a rating of 2 or less.

Example 3: Two Dip Process (Epoxysilicone / Aminopropyltriethoxysilane)

Corks were dipped into an epoxysilicone solution and then into a 0.1% solution of Aminopropyltriethoxysilane in water. The coating was allowed to cure at 40°C for 1 hour.

Sensory evaluation tests gave a rating of 2 or less. Scanning Electrode Microscopy (SEM) showed an obvious smooth layer of coating (Fig 1A). The coating was undisturbed after a compression test (Fig 1B) and there was no visible deterioration of the coating even after being immersed in white wine for 24 hours (Fig 1C).

Example 4: Polyethylene/Polyethylene Vinyl Alcohol/Polyethylene Laminate Film A polyethylene/polyethylene vinyl alcohol/polyethylene laminate film was wrapped around the cork and sealed with a heat gun.

Sensory evaluation tests gave a rating of 2 or less.

Example 5: Poly(Dimethylsiloxane-alt-Diphenyl)Copolymer

Poly (dimethylsiloxane-alt-diphenyl) copolymer was synthesised as described in: Clarke, S.; Graiver, D.; Matisons, J.; and Owen, M., US Patent Appl. DC4689 1999 and EP Pat Appl. 993 093 48.3. The corks were dipped in a 25% solution of the polymer with hexane. The hexane was removed by evaporation in an oven at 60°C for 24 hours.

Sensory evaluation tests gave a rating of 2 or less.

Example 6: Polyacrylate / Methacrylate

A cork was dipped into a solution of 46% acrylic methacrylic acid ester in water and then allowed to dry in a 40° C oven overnight. The coated cork was then submitted for testing.

Sensory evaluation tests gave a rating of 2 or less.

Example 7: Polyvinylacetate Emulsion/Aminosiloxane Emulsion

The cork was dipped into a solution consisting of 75% Polyvinylacetate emulsion and 25% Aminosiloxane emulsion. The coating was then cured in an oven at 38°C for 1 hour. The coated cork was then submitted for testing.

Sensory evaluation tests gave a rating of 2 or less.

Example 8: Polyvinylacetate/Polymethylhydrogen Siloxane Emulsion

The coating formulation consisted of a mixture of 75mL of polyvinylacetate emulsion (PVA) and 25mL of polymethylhydrogen siloxane emulsion. 100 corks were placed into a tumbler and 20mL of the coating formulation was distributed casually over the corks. The corks were tumbled, to evenly distribute and dry the coating, for 1 hour at 40 °C.

Sensory evaluation and Gas Chromatography/Mass Spectroscopy (GC/MS) results showed that no TCA or other undesirable odours were detected.

In particular, sensory evaluation tests gave a rating of 2 or less.

The SEM showed a visible uniform coating on the surface of the cork (Fig 2A). The coating was also visible in cracks on the surface of the cork (Fig 2B). Analysis of the coating after it had been immersed in white wine for 24 hours showed that the coating was still present and intact (Fig 2C). After compression in a commercial hand corking device, the coating still formed a continuous layer (Fig 2D).

WASHING PROCEDURE

Corks can be rinsed or soaked with hot or cold water, alcohol, or a mixture of both water and alcohol, before the coating is applied. This reduces the occurrence of taint and other unwanted odours by washing away any taint compounds already on the surface of the cork. It is thought that any surface taint could mix with the coating during the coating process and remain on the surface of the coating, thus contributing to, rather than preventing, the taint problem. Accordingly, it is preferable to carry out a washing procedure, eg as in Example A, B, C or D below, prior to coating corks. The corks are then dried, eg in an oven at 40°C for 24 hours, prior to being coated.

Example A

Corks spiked with 100mg/L of TCA in absolute ethanol were arranged in a single layer and passed through streams of hot water for 30 seconds and then allowed to dry.

Sensory evaluation tests gave a rating of 2 or less.

Example B

Corks spiked with 100mg/L of TCA in absolute ethanol were arranged in a single layer and passed through streams of liquid containing cold water and absolute ethanol and then allowed to dry.

Sensory evaluation tests gave a rating of 2 or less.

Example C

Corks spiked with 100mg/L of TCA in absolute ethanol were completely immersed in a solution of hot water for 30 minutes and allowed to dry.

Sensory evaluation tests gave a rating of 2 or less.

Example D

Corks spiked with 100mg/L of TCA in absolute ethanol were completely immersed in a solution containing a mixture of cold water and absolute ethanol.

Sensory evaluation tests gave a rating of 2 or less.

METHODS OF APPLICATION

Dip Coating

The simplest application method is dip coating, involving a container filled with the coating formulation into which the substrate (such as a cork) is immersed and then withdrawn

A typical dip coating unit consists of a bath, filled with the coating formulation, and a mechanism on which the substrate is mounted for immersion and withdrawal. It is often necessary to circulate and filter the coating to maintain a homogeneous mixture. A fixing mechanism must be designed to ensure the proper orientation of the substrate during immersion into and withdrawal from the fluid.

Spray Coating

In contrast to dip coating, spray coating operations are much less efficient and much more complicated, as well as being relatively more expensive. Precise control over the spray area is difficult so that masking of the substrate may be required. The advantages offered by these systems (eg fast application time, very uniform coating

7.

thicknesses, and the ability to apply uniform coatings to irregularly shaped objects) may, however, outweigh the drawbacks.

In a spray coating operation, the fluid is atomised into fine droplets for application to the substrate. The size of the droplets formed during atomisation can be controlled by such properties as fluid flow, fluid pressure, air pressure, solution viscosity, and surface tension. A number of different nozzle designs are used in industry, such as compressed air spray nozzles, airless spray nozzles, and hot spray systems.

Slot and Curtain Coating

Slot coating and curtain coating are more appropriate techniques for a continuous operation. The methods involve a stationary die, which delivers a layer of coating onto a substrate moving beneath it. The difference between the methods is in the way that the coating is transferred from the die to the moving substrate. The coating is spread by the slot method when the die slot is close to the substrate; but changing the orientation of the die slot relative to the conveyor and allowing the formulation to cascade is referred to as curtain coating.

Multiple slots in the die face or converging feed to a single slot can produce multilayer coatings.

Roll Coating

Roll coating is another method used in continuous manufacturing operations primarily for coating films. A substrate is fed between two rotating cylinders, while simultaneously directing the coating into the space between the cylinders. Formulation viscosity, speed of the substrate, coating flow rate, and distance between the rolls all contribute to coating thickness and uniformity. Although these systems are limited in the types of substrate that can be coated, they can rapidly produce a very uniform product.

METHODS OF CURING

Thermal Cure

One of the most common methods for initiating the cross-linking of a polymer is by heating, and ovens can be incorporated into batch and continuous-mode systems. The main disadvantage in thermal curing is the wasted thermal energy when only a small amount of the applied energy is transferred to the molecules. It can also be difficult to maintain a uniform temperature throughout the oven, so that curing may be uneven.

Ultraviolet (UV) Cure

One of the most popular techniques used to initiate cross-linking is irradiation by ultraviolet light. It can be a more rapid process than thermal curing, sometimes taking less than a second to act. Very little heat is generated during the exposure, which can often be carried out at room temperature.

Electron Beam Cure

Electron beam (E-beam) radiation shares the same benefits as UV radiation, without the need for a photoinitiation. The exposure forms free radicals that cause the chain reaction.

Gamma-Radiation Cure

Yet another type of irradiation that is rapid at ambient temperatures is γ -radiation cure. Cycle times for γ -ray systems can be longer than for E-beam, at least for conventional polymer matrices, but for curing hydrophilic coatings this does not present a problem.

ADDITIONAL TECHNOLOGIES

Plasma Polymerisation

Thin polymer films can be deposited onto various substrates through the use of plasma polymerisation. A plasma is generated by means of electron excitation, with a gas mixture and an organic monomer. These thin films can be between a few hundred angstroms to a micrometre in thickness. Cross-linking density is usually greater than in conventionally applied coatings, and thin films exhibiting good adhesion can be laid down on virtually any type of substrate.

14

Surface Grafting

Surface grafting techniques incorporate some of the same general concepts as coating and curing operations but may be more appropriate where exceptionally thin surface layers are desired. Points that distinguish surface grafting from "wet" coating operations are related mainly to the formation of the modified surface layer and the general molecular structures that result. In conventional coatings, a continuous phase is formed by the reactions of the monomeric or polymeric ingredients, and is adhered to the substrate surface through secondary molecular interactions such as hydrogen bonding, London dispersive forces or acid-base interactions. Primary covalent bonding is also possible if the substrate has been pre-treated with molecular groups. In surface grafting however, the monomeric (or polymeric with reactive end groups) components react directly with a polymeric substrate. Various forms of radiation, such as UV, electron beam, and γ -rays, may be used to cause the formation of peroxide groups on the polymer surface. These are unstable so decompose, and cause initiation of polymerisation in the process.

While the present invention has been described in terms of preferred embodiments in order to facilitate better understanding of the invention, it should be appreciated that various modifications can be made without departing from the principles of the

invention. Therefore, the invention should be understood to include all such modifications within its scope.

WO 00/64649 PCT/AU00/00367

16 THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

- 1. A method for producing a coating or diffusion layer on a substrate for use in contact with a food product or beverage, said coating or diffusion layer preventing or inhibiting passage therethrough of flavour-active or odour-active compounds, and said method comprising applying to the surface of said substrate an effective amount of a copolymer comprising a flexible component and a retentive component, said flexible component being sufficiently flexible to allow the coated substrate to undergo compression and recovery and said retentive component being able to bind with or otherwise retain flavour-active or odour-active compounds.
- A method according to claim 1, wherein said substrate is a bottle closure, packaging or wrapping material, or a bottle or other container.
- 3. A method according to claim 1, wherein said substrate is a natural or synthetic cork, and said coating or diffusion layer prevents or inhibits passage of flavour-active or odour-active compounds from said cork to an alcoholic beverage in contact with said cork.
- A method according to claim 3, wherein said flexible component is sufficiently flexible to allow the coated cork to be compressed and then to recover during a bottling process.
- A method according to claim 1, wherein said flavour-active compounds are trichloroanisoles (TCA).
- A method according to claim 1, wherein said copolymer is a graft, alternating or block copolymer.

17

- A method according to claim 1, wherein said flexible component is formed from silicon-based monomers.
- 8. A method according to claim 1, wherein said copolymer is a polyvinylacetate (PVA) copolymer, a polyurethane copolymer or ionomer, a terephthalate copolymer, a styrene-acrylonitrile (SAN)/ acrylonitrile-butadiene-styrene (ABS) copolymer, a (vinylidene) copolymer, an epoxy copolymer, an amide copolymer, a Bisphenol copolymer, a Bisphenol A (BPA) epichlorohydrin copolymer, a poly (methyl) methacrylate copolymer, a poly(methacrylic acid) copolymer, a cellulose copolymer, a polyethylene vinyl alcohol copolymer, a silane copolymer or a siloxane copolymer.
- A method according to claim 8, wherein said copolymer is a polyvinylacetate (PVA) copolymer.
- 10. A method according to claim 8, wherein said copolymer is a silane or siloxane copolymer, comprising polyethyleneglycol (PEG), isoprene, butadiene, lactone, amino, terephthalate, amino acid, heterocyclic, hydride (SiH), thiol or epoxy functionalities.
- 11. A coated substrate produced according to the method of any one of claims 1 to 10.
- 12. A coated cork produced according to the method of any one of claims 1 to 10.
- 13. A method according to any one of claims 1 to 10, substantially as described herein and with reference to any one of Examples 1 to 8.
- 14. A coated substrate according to claim 11, substantially as described herein and with reference to any one of Examples 1 to 8.

ADDOUGH TOURS


15. A coated cork according to claim 12, substantially as described herein and with reference to any one of Examples 1 to 8.


PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau




(51) International Patent Classification 7:	A1	(11) International Publication Number: WO 00/64649	
B27K 7/00, B67B 1/03		(43) International Publication Date: 2 November 2000 (02.11.00)	
(21) International Application Number: PCT/AU		of South Australia, The Levels Campus, Mawson Laker	
(22) International Filing Date: 20 April 2000 (3 (30) Priority Data: PP 9894 22 April 1999 (22.04.99)		(74) Agent: MADDERNS; Level 1, 64 Hindmarsh Square, Adelaide, S.A. 5000 (AU).	
		GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR,	
use in contact with a food product or beverage, said coatin cork to an alcoholic beverage) of flavour-active or doour-a applying to the surface of said substrate an effective amous said flexible component being sufficiently flexible to allow a coated cork according to the present invention to be co	ng or di ctive con nt of a the con ompress	producing a coating or diffusion layer on a substrate (e.g. a cork) for fusion layer preventing or inhibiting passage therethrough (e.g. from a mpounds (commonly known as cork taint), and said method comprising popolymer comprising a flexible component and a retentive component, and the substrate to undergo compression and recovery (e.g. so as to allow dand then to recover during the bottling process) and said retentive or ordour-active compounds. In a second aspect, the present invention	









WO 00/64649 PCT/AU00/00367





FIG 2B



WO 00/64649 PCT/AU00/00367

4 / 4

ACCV Spot Magn Det WD Exp 29:1 200 µm
FIG 2D



Attorney's Docket No: 2625-1-002

COMBINED DECLARATION/POWER OF ATTORNEY

AS BELOW NAMED INVENTORS, WE HEREBY DECLARE THAT: This Declaration is of the following type:					
Original Divisional	Supplemental Continuation	Continuation-In-PartX National Stage of PCT			
Our residence, post office addresses and citizenship are below next to our names; We believe we are the original, first and sole inventor (if only one name is listed below) or the original, first and joint inventors (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: "TREATED CLOSURES 3" the specification of which:					
is attached hereto was filed on , as Serial No was amended on (if applicable) X was described and claimed in PCT International Application No PCT/AU00/00367 filed on 20th April 2000 and was amended under PCT Article 19 on					
We hereby state that we have reviewed and understand the contents of the above- identified specification, including the claims, as amended by any amendment					

We hereby state that we have reviewed and understand the contents of the aboveidentified specification, including the claims, as amended by any amendment referred to above. We acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Sec. 1.56(a).

We hereby claim foreign priority benefits under Title 35, United States Code, Sec.119 of the foreign application(s) for patent or inventor's certificate or of any PCT International application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America files by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

Country	Appln No.	Day/Month/Year/Filed	Priority Claimed Yes No
Australia	PP 9894	22 nd April 1999	YES

We would have been doubt fired. He

We hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the U.S. Patent and Trademark Office connected with:

Klauber & Jackson
Continental Plaza
411 Hackensack Avenue
HACKENSACK NJ 07601US A

We hereby declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issue therefrom.

Phillip MACKIE Pull rame of first inventor 74 V. Work Roan Mount Barken Residence South Australia 5251	Date Australia Citizenship
Post Office Address Darren LANGE Full name second inventor Inventor's signature	23/0/01
SON ANSWALLA SIB	ASSECIAN Citizenship
Post Office Address Russell IOFINSON Full name third inventor Inventor's signature	18/10/2004 Date
93 Penace Ross Ancideral. Residence Som Associa 9353, All Post Office Address	Averena J Citizenship

.../3

	1.55.1	
Leanne BRITCHER	Lly Britcher	23/10/01
Full name fourth inventor	Inventor's signature	Date'
10 Albany Toe Valley	, View SA 5093	AUSTRALIAN
Residence	N /	Citizenship
	NUN	
Post Office Address		
Janis MATISONS		
Full name fifth inventor	Inventor's signature	Date
Residence		Citizenship
		Спистыя
Post Office Address		
Tost Office Address	$\mathcal{L} \cap \mathcal{A}$	
	7/4/1/4	22/1-/21
Terry WILKS Full name sixth inventor	Inventor scienature	23/10/01
/		A
2/94 YNTE STREE	T NORTH ADELANDE SA STOOL	HUSTRALIAN
Residence	All	Date Aug-TRALIAN Citizenship
	W	
Post Office Address		
	1 1 44.	, ,
Rosalind MA	Kosaliyathla	23/10/01 Date
Full name seventh inventor	Kosaliya Ma Inventor's signature	Date
5/32 KINTORF AVE	PROSPECT SA SO82	<u>AUSTRALIA</u> N
Residence	TRUST FET ST COS E	Citizenship
	DW	r
Post Office Address	``\	
rost Office Address		
	// i M	1-1.
Mark FRANSON Full name eighth inventor	Inventor's signature	23/10/01
•		A a .
41 STILLWELL COURT	CREENWITH SA 5125	HUSTRALIAN
Residence	Λ	Citizenship
	HUNL	
Post Office Address	404	


Residence

Post Office Address

Citizenship

-3-Full name fourth inventor Inventor's signature Date Citizenship Post Office Address Janis MATISONS
Full name fifth inventor 3 Fe Har Ave. South Australia Marion 5043 AUSTRALIAN Residence Citizenship AS ABOVE Post Office Address Terry WILKS
Full name sixth inventor Inventor's signature Date Residence Citizenship Post Office Address Rosalind MA Full name seventh inventor Inventor's signature Date Residence Citizenship Post Office Address Mark FRANSON Full name eighth inventor Inventor's signature Date

United States Patent & Trademark Office Office of Initial Patent Examination -- Scanning Division



for scanning.

□ Page(s)	of	were not present

· Scanned copy is best available. JYAWING MOST FIG AYEVERYDOYL

(Document title)

(Document title)

were not present